SNAP MARKETING · B2B COMMERCIAL EQUIPMENT & PANTRY

ATLANTIS COMMERCIAL VENDING MACHINES

Automatic Bean-to-Cup, Multi-Option Premix & Coffee Capsule Systems

INSTITUTIONAL HOT BEVERAGE DISPENSERS FOR HIGH-FOOTFALL CORPORATE WORKPLACES

PRODUCT SPECIFICATIONS MATRIX

MODEL / SKU	PRODUCT NAME	DISPENSING TYPE	LANES / CANISTERS	SPEED / OUTPUT
ATL-BREW-B2C	Atlantis Brew Automatic Machine	Bean-to-Cup	Fresh Beans + 2 Canisters	Fresh Milk & Steam
ATL-SELECT-4L	Atlantis Select 4-Lane Dispenser	Premix Powder	4 Drink Options	Up to 5 Cups / Min
ATL-CLASSIC-2L	Atlantis Classic 2-Lane Dispenser	Premix Powder	2 Drink Options	Compact Footprint
ATL-CLASSIC-3L	Atlantis Classic 3-Lane Dispenser	Premix Powder	3 Drink Options	High Output
ATL-NEO-2L	Atlantis Neo Modern Dispenser	Premix Powder	2 Drink Options	Digital Temp Control
ATL-NEO-4L	Atlantis Neo 4-Lane Dispenser	Premix Powder	4 Drink Options	Microprocessor Board
ATL-COIN-VEND	Atlantis Coin-Operated Vending	Coin Token / Cash	3 Canisters	Self-Service Vending
ATL-JAZZ-CAPSULE	Atlantis Jazz Coffee Capsule Unit	Capsule Pods	Compatible Pods	19-Bar Italian Pump

TECHNICAL & OPERATIONAL ADVANTAGES

Precision Digital Temperature Control

Maintains optimal 85-90°C extraction temperature for peak tea and coffee flavor.

Anti-Caking Whipper Chambers

High-speed centrifugal whippers ensure smooth, frothy beverages with zero residue.

Digital Audit Cup Counter

Tracks dispensed cup counts per drink option for precise workplace consumption budgeting.

Full Stainless Steel Construction

Durable commercial chassis built for continuous round-the-clock office operation.

ENTERPRISE PANTRY SUPPLY & BULK FULFILLMENT

SNAP MARKETING PRIVATE LIMITED · AUTHORIZED CORPORATE PANTRY DISTRIBUTOR

Head Office: Snap House, 322/16, Shankar Sheth Road, Hotel 7 Loves Chowk, Pune, Maharashtra 411042

Direct Corporate Desk: +91 98230 12724 | Email: sales@snapmktg.com | Web: www.snapmktg.com

GST Registered Enterprise | Direct Manufacturer Warranty | Genuine Consumables Guaranteed

© 2026 Snap Marketing Pvt Ltd. All specifications subject to standard manufacturer tolerance.